




Orbital Ka-Band LNB with Multiple Local Oscillators



This Ka-band low noise block downconverter (LNB) uses multiple local oscillators to let you switch between different Ka frequency bands in the 19.20 to 21.20 GHz range. It provides user bandwidth of up to 1 GHz and offers exceptional performance for commercial and military satellite communication (SATCOM) applications.

- Switchable between different Ka frequency bands
- Local or remote band switching for flexibility in the field
- Flat frequency response for higher-order modulation schemes
- High data throughput and low bit error rate (BER)
- Internal isolators for impedance matching and maximum signal transfer
- Options for high temperatures and temperature-compensated gain

The external reference LNB supports Global Xpress (GSX) and Wideband Global SATCOM (WGS) configurations as well as commercially available Ka High Throughput Satellites (HTS). It delivers the gain, phase noise and linearity needed to handle higher-order modulation schemes in both the GEO and LEO satellite markets. Used in ARSTRAT qualified Terminals.



FREQUENCY RANGE

RF Frequency Band (GHz)	19.2 to 21.2
IF Frequency Band (MHz)	950 to 2100
Bandwidth (MHz)	1 GHz bands
Local Oscillator (GHz)	17.25 to 20.25
Noise Figure (dB)	1.5 max
LO Stability	Locked to external reference
LO Phase Noise	Locked to external reference
Band Switching	Voltage

10 MHz REFERENCE

Insertion	via input connector
Input Level	-10 to 0 dBm

VSWR

Input	1.3:1
Output	2.0:1

GAIN

Gain (dB)	60
Flatness	+/- 1.5 dB over frequency
Ripple	+/- 0.3 dB over any 10 MHz
Stability	+/- 0.25 dB over 24 hrs @ 25C

OTHER SPECS

Image Rejection	-40 dBm min
LO Leakage	-45 dBm
1 dB Compression (dBm)	+10 min
OIP3 (dBm)	+20 min
Desense Level	-50 dBm transmit signal results in no more than 0.1 dB of NF degradation

ENVIRONMENTAL

Operating Temp	-40°C to +60°C
Humidity	100% condensing
MTBF	> 250,000 hours
Standards	RoHS and REACH

POWER

Current Draw	5 watts max
Input Voltage Range	15 to 26 VDC

MECHANICAL

Weight (grams)	485
Length (mm)	145
Width (mm)	44
Depth (mm)	44
Input Connector	WR-42
Output Connector	N or SMA

OPTIONS

Push button band switching
RS 422 via micro DB9 switching
Extended temperature ranges

PUSH BUTTON BAND SWITCHING



Please contact Orbital Research for ordering information: sales@orbitalresearch.net